

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

1-23. (Cancelled)

CI 24. (New) An assembly configured for attaching to a vehicle, the vehicle including a steering structure including clamp members, the assembly comprising:

a curved unitary handlebar; and

a first and a second handlebar riser, each riser including:

an upper handlebar connecting structure adapted and configured to selectively connect the curved unitary handlebar to the riser member and allow for selective rotation of the handlebar about a first axis for adjustment of the orientation of the handlebar in relation to the vehicle; and

a vehicle connecting structure adapted and configured to selectively connect the riser member to the existing steering structure of the vehicle utilizing the clamp members of the steering structure, and allow for selective eccentric rotation of the riser member about a second axis to allow for height and position adjustment of the handlebar in relation to the vehicle.

25. (New) The assembly of claim 24, wherein the vehicle connecting structure of each handlebar riser comprises a cylindrical projection extending perpendicularly from each handlebar riser.

26. (New) The assembly of claim 24, wherein the handlebar connecting structure of each handlebar riser comprises an upper surface of the handlebar riser including an indentation configured to accept the curved unitary handlebar and a separate upper clamp portion that is configured to be secured to the upper surface of the handlebar riser, thereby securing the curved unitary handlebar.

27. (New) The assembly of claim 26, wherein the handlebar connecting structure of each handlebar riser is configured to permit placement of the curved unitary handlebar atop the indentation of each upper surface, with the separate upper clamp portion of each handlebar riser subsequently secured to the handlebar riser.

28. (New) A riser assembly for attaching a unitary handlebar to a vehicle, the handlebar having a generally cylindrical cross section defining a diameter, the vehicle including a steering structure including clamp members, the riser assembly comprising:

01 a first handlebar riser and a second handlebar riser, each of the two riser including:

a riser body having a length that is greater than the diameter of the handlebar and having an upper portion and a lower portion;

an upper handlebar connecting structure disposed at the upper portion of the riser body, the upper handlebar connecting structure including an upper surface of the riser body including an indentation configured to accept a portion of the unitary handlebar, and a separate upper clamp portion that is configured to be secured to the upper surface of the handlebar riser, thereby selectively securing the unitary handlebar to the riser body for selective rotation of the handlebar about a first axis for adjustment of the orientation of the handlebar in relation to the vehicle;

a vehicle connecting structure disposed at the lower portion of the riser body and spaced from the upper handlebar connecting structure by a distance greater than the diameter of the handlebar, the vehicle connecting structure of each of the risers including a cylindrical projection extending from each of the riser bodies, the projections sized and shaped to selectively connect the riser member to the existing steering structure of the vehicle utilizing the clamp members of the steering structure, and allow for selective eccentric rotation of the riser member about a second axis to allow for height and position adjustment of the handlebar in relation to the vehicle.